

Research and Technology Activities Supporting Closed-Brayton-Cycle Power Conversion System Development

Michael J. Barrett
NASA Glenn Research Center
Cleveland, OH 44135
Michael.J.Barrett@nasa.gov

The elements of Brayton technology development emphasize power conversion system risk mitigation. Risk mitigation is achieved by demonstrating system integration feasibility, subsystem/component life capability (particularly in the context of material creep) and overall spacecraft mass reduction. Closed-Brayton-cycle (CBC) power conversion technology is viewed as relatively mature. At the 2-kWe power level, a CBC conversion system Technology Readiness Level (TRL) of six (6) was achieved during the Solar Dynamic Ground Test Demonstration (SD-GTD) in 1998. A TRL 5 was demonstrated for 10 kWe-class CBC components during the development of the Brayton Rotating Unit (BRU) from 1968 to 1976. Components currently in terrestrial (open cycle) Brayton machines represent TRL 4 for similar uses in 100 kWe-class CBC space systems. Because of the baseline component and subsystem technology maturity, much of the Brayton technology task is focused on issues related to systems integration. A brief description of ongoing technology activities is given.

Research & Technology Activities Supporting Closed-Brayton-Cycle Power Conversion System Development

Michael Barrett
NASA-GRC

Lee Mason, Tony Baez, Dave Hervol, Duane Beach,
John Gayda, Cheryl Bowman, Frank Ritzert,
Jay Singh, Chris Dellacorte, John Lucero

2nd International Energy Conversion Engineering Conference
Providence, Rhode Island USA
August 16, 2004


Glenn Research Center

at Lewis Field





Acknowledgment


Project Prometheus, NASA's Nuclear Systems Program, supported the work described within this presentation, in whole or part, as part of the program's technology development and evaluation activities. Any opinions expressed are those of the authors and do not necessarily reflect the views of NASA, Project Prometheus or the JIMO Project.




Some Nuclear Electric Power Possibilities



Landers




Surface Bases



Interplanetary Spacecraft

Glenn Research Center

at Lewis Field



Some Advanced Power Conversion Challenges

1. Multiple year operation

- High reliability components & systems
- Long life materials with conservative design margins
- Hermetic sealing to prevent fluid leakage

2. Generate power ~200X that of previous U.S. nuclear-fission space system

- High-power static-conversion designs
- Alternative dynamic-conversion approaches

3. Rapid and rigorous development

- Focused development programs
- High-TRL component technologies

4. Provide minimum mass designs


- High-temperature operation
- Alternative lightweight materials
- System-level mass optimization

5. Operate in severe environments

- Radiation-tolerant materials and components
- Micrometeoroid/Orbital Debris (MMOD) and Atomic Oxygen (AO) protection

6. Assure mutually compatible interfaces with reactor, heat rejection, and PMAD


- Effective inter-agency (NASA/DoE) & government/industry teaming relationships
- Strong system engineering & integration



SNAP-10A (USA, 1965)

Glenn Research Center

at Lewis Field




R&T for Closed-Brayton-Cycle (CBC) Power Conversion

- Current Power Conversion Subsystem R&T effort is focused on risk-reduction activities


- Focus Areas

- Power Converter Subsystem
- Power Conditioning & Distribution Subsystem
- Heat Rejection Subsystem
- Power Conversion System Materials












Glenn Research Center

at Lewis Field



Space Brayton History



- 10 kW Brayton Rotating Unit (BRU)
- 2 kW Mini-BRU
- 1.3 kW Brayton Isotope Power System (BIPS)
- 100 kW to MW Class NEP Concepts

- 25 kW Space Station Freedom Solar Dynamic (SD) Power Module
- 20 kW SP-100 Design

- 2 kW SD Ground Test Demonstration
- SD-Mir Flight Experiment
- 0.5 to 6 kW Dynamic Isotope Power System (DIPS)

- 100 kW-Class NEP Concepts
- 2 kW Brayton Testbed
- 55 watt Micro-Turbine

1970


1980

1990

2000


Glenn Research Center

at Lewis Field




2-kWe Brayton Converter Unit

- Existing 2-kW Brayton Unit Available for NEP Risk Reduction
 - SD GTD Brayton Converter
 - Electrical Gas Heater
 - Commercial Chiller
 - Alternator Test Rig (ATR)
- Tasks Completed
 - Replaced SD Receiver w/Gas Heater
 - Designed & Assembled New (In-House) Electrical Controller
 - Completed Initial Checkout & Performance Mapping (June '02)
 - Designed & Assembled 1100 Vdc Transformer-Based Controller for Ion Thruster Demo
 - Ion Thruster (NSTAR) Demo
- Current Plans
 - Mechanical Dynamic Modes Test (FY04)
 - Thermal Transient Modes Test (FY05)
 - Integrate & Test Advanced Radiator (FY06)




2 kW Brayton/
NEP Testbed


Evaluate Control
Methods & Transient
Thermal Response




Demonstrate
High Voltage
Distribution



Characterize
Ion Thruster
Interactions



Demonstrate
Composite
Radiator
Technology






Glenn Research Center

at Lewis Field




Brayton NSTAR Test Layout





Glenn Research Center

at Lewis Field




Test Results

- Stable thruster operation demonstrated at all test points
- Demonstrated high AC-to-DC conversion efficiency
- High-speed load switching from ion thruster to PLR during thruster recycles



Glenn Research Center

at Lewis Field



Alternator Test Unit

Objective - Design, build, and test a high speed 25-100 kWe Closed Brayton Cycle Alternator Test Unit to examine and characterize electrical performance and interactions with the balance of an NEP electrical system.

- **Phase 1 - Alternator Design Studies (6 mo.)**

- Perform trade studies to evaluate alternator design options over a range of potential operating parameters (see table)
- Develop an ATU conceptual design including drive system and electrical controller

- **Phase 2 - ATU Fabrication and Test (15 mo.)**

- Complete a detailed design and fabricate the ATU, drive system, and controller
- Perform operational checkout of ATU at contractor facility
- Deliver ATU, drive system, and controller to NASA GRC for integration into High Power PMAD Testbed

- **Status**

- Phase 1 contracts awarded (Hamilton-Sundstrand, Honeywell)
- Phase 1 concluding: trade study prelim results and concept designs
- Phase 2: detailed design Jan 05; hardware delivery Jan 06

Design Parameter	Values
Net Alternator Power, kWe	25, 50, 100
Line-to-Line Voltage, Vrms	400, 4000
Operating Speed, RPM	30000, 60000
Number of Magnetic Poles	2, 4, 6, 8

Glenn Research Center

at Lewis Field



High Power PMAD


Objective – Design and develop a high power breadboard PMAD system to support technology development and design activities associated with the development of a generic NEP-Brayton spacecraft system for deep-space applications

Note: not the Jupiter Icy Moons Orbiter (JIMO) Gov't PMAD design


- Initial Capability
 - Built using readily available, off-the-shelf components
 - Supports trade studies and technology development activities
- Final Configuration
 - Breadboard hardware; spacecraft-like architecture option
 - PMAD design verification testbed
 - Characterize electrical performance of ATU
 - Representative PPU and Bus load accommodation
 - ATU / PPU / Ion thruster end-to-end characterization tests
- Status
 - Preliminary design complete (initial capability stage)
 - Description document distributed
 - Initial configuration in fabrication
 - Final configuration design ongoing

Glenn Research Center

at Lewis Field




High Power PMAD Initial Capability Configuration



Note: Not the JIMO Gov't PMAD design




Glenn Research Center

at Lewis Field



Turbomachinery

- **Advanced rotor/wheel conceptual design studies**
 - Task scheduled for FY05
 - Advanced aero design configurations
 - Advanced materials options (Si_3N_4 , C-C)




Ceramic (Kyocera) gasifier turbine
in IR Powerworks machine

- **Integrated wheel/shaft/bearing design, development & test**
 - Use existing DD&T capability at GRC

Glenn Research Center


at Lewis Field



Bearing Technology

- **Material Selection**


- Low/Moderate Temp: Graphite, Moly Disulfide, Teflon, Polyimides
- High Temp: PS100 (NiCr-Glass), PS200 (NiCo-Cr₃O₂), PS304 (NiCr/CrO₃ + Ag, BaF₂/CaF₂)
- Application Processes: Sprays, Power Metallurgy, Thin Films



NASA PS304

- **Testing**

- Friction & Wear Rigs (Pin on Disk, Pin on Plate)
- Elevated Temperatures
- Controlled Atmospheres (e.g. HeXe)




Journal Test Rig

- **Post-test Analyses**


- Wear Measurements
- Optical Microscopy/Profilometry
- Electron, X-ray Examination

- **Performance Characterization**

- Start / Stop Torques
- Bearing Preload
- Power loss and Heat Generation
- Load Capacity and Sizing
- Durability and Life
- Radiation Effects




Controlled Atmos. Test Rig



Speed and Torque Trace





Glenn Research Center

at Lewis Field



Heat Exchangers

- Heat exchanger modeling
 - In-house code upgrades completed
- Carbon-carbon recuperator study
 - IECEC 2004 Paper
- Hot side heat exchanger options
 - Study ongoing; report Sept 04
- Gas coolers
- University grant (Penn St/ARL)
 - Advanced materials
 - Constructal-formulation-based design
 - Integral design/CFD analysis capability
- Upgraded GRC HX test facility
 - Ambient & thermal-vac test capability
 - Mods ongoing; July 05 completion
- DoD technology leveraging
 - SBIR with Allcomp; C-C plate-fin HXs



Glenn Research Center

at Lewis Field



Radiator Demonstration Unit

Objective - Design, build, and test a radiator using advanced materials and heat spreading technology to characterize and demonstrate heat rejection performance over a range of temperatures applicable to dynamic power conversion options.


- **Phase I - RDU Design Trade (6 mo.)**

- Two six-month RDU contracts awarded to conduct trade studies evaluating advanced radiator designs and develop a conceptual design
 - Advanced Cooling Technologies
 - Lockheed Martin Space Systems Company
- Design Reviews: Apr/Jun '04
- Trade Studies Complete: Jun/Aug '04
- High Temperature (500/550 K) water heat pipe life tests underway at ACT.

- **Phase 2 - RDU Fabrication and Test (16 mo.)**


- Validate manufacturing and design approach through development and test of RDU
- Deliver RDU to NASA GRC for stand-alone and integrated thermal vacuum tests with 2kW_e CBC test-bed
- Design Reviews: Jan '05
- Final Design Reports: Oct '05
- Thermal/Vacuum Tests at GRC Tank 6 : Feb '06

Design Parameter	Values
Heat Load, kWt	200, 400, 800
Radiator Outlet Temperature, K	300, 350, 400
Radiator Fluid ΔT , K	100, 150
Sink Temperature, K	200





Glenn Research Center

at Lewis Field




Carbon-Carbon Composites

- **Carbon-Carbon provides low density, high conductivity, high strength material for various uses:**
 - Radiator Panels
 - Heat Exchangers
 - Structures and Armoring
- **GRC Addressing Two Key Areas for Carbon-Carbon Implementation**
 - C-C to Metallic Brazing and CTE Mismatch Resolution (req'd for fluid system integration)
 - C-C Manufacturing Processes Using Melt Infiltration and Fiber Reinforcement
- **Expected Deliverables**
 - C-C Manufacturing Survey
 - Experimental Brazing Trials & Evaluation
 - C-C Materials with Tailored Properties
 - Transfer of Brazing and Assembly Technology to Vendors
- **Leverage Current Aero Programs**
 - Affordable Fiber Reinforced Ceramic Composites (AFReCC)
 - Affordable, Robust Ceramic Joining Technology (ARCJoinT)



Ceramic Composites with Silicon Melt Infiltration

Ceramic Joining Examples





Glenn Research Center

at Lewis Field




Creep Testing

- **Conduct Broad Test Series of Potential Materials in Air Creep Rigs**
 - Cast Superalloys (e.g. MAR-M247)
 - Wrought Superalloys (e.g. LSHR Alloy)
 - Alternatives (e.g. TiAl, Silicon Nitride)
- **Selected Testing in new State-of-the Art Inert Gas Test Rigs**
 - 273 To 1300 K
 - 200 kg To 4,500 kg
 - Dual Strain Transducers with >100 Microstrain Resolution
 - Scheduled for FY04 Operation
- **Extrapolation Of Creep Data**
 - Test Candidate Materials Over a Wide Range of Temperatures and Stresses
 - Utilize Larson-Miller Parameter to Extrapolate Creep Data to Potential Mission Durations
- **Possible Testing of Bi-metallic Joints and Irradiated Material Samples**




Glenn Research Center

at Lewis Field




Refractory Metal Interface

- Two Primary Concerns:
 - Contaminant Transport from Superalloy to Refractory via HeXe Working Fluid
 - Superalloy-to-Refractory Joints
- Contaminant Transport (e.g. O, N, C) Addressed through Superalloy Processing
 - Formation of Alumina on Surface Provides Protection Against Constituent Transport
 - Analysis Shows Partial Pressures of O_2 (10^{-38} torr) below Nb-1Zr Threshold (10^{-9} torr)
 - Experimental Verification in Work
- Electron Beam (EB) Welding Identified as Joining Approach
 - Solid-Solution Strengthened Hastelloy X + Nb-1Zr Initial Candidates
 - Others to be considered (e.g., INCO 617 + Nb-1Zr)
- Critical Process Elements include:
 - Long-term Stability And Deleterious Phase Formation
 - Working Fluid Exposure
 - Post-Weld Heat Treatment and Mechanical Properties



Glenn Research Center

at Lewis Field



Technology Summary

Brayton Technology Efforts are Addressing Risk Areas

- Historical space system development and contemporary terrestrial systems inform current Brayton technology efforts
- 2-kWe test bed provides valuable tool for assessing power control, distribution and overall system integration issues
- Alternator Test Unit and Radiator Demonstration Unit address critical component technologies
- Turbomachinery, Bearing, and Heat Exchanger tasks complement potential industry development activities
- Materials Research will guide conversion system design, manufacturing, assembly, and life validation

Glenn Research Center

at Lewis Field

